

# Declaration of Performance (DoP)

| No. Jøtul F 480-CPR-140618  |   |
|---|---|
| <b>Product Type:</b>  | Roomheaters fired by solid fuel   |
| <b>Type, batch or serial number:</b>  | <b>Jøtul F 480 Series</b><br>(Jøtul F481, Jøtul F 483)  |
| <b>Intended use of the product:</b>   | Roomheater burning solid fuel without water supply<br>Fuel type: Wood                                       |
| <b>Name and Address of the manufacturer:</b>  | Jøtul AS<br>Postboks 1411, 1602 Fredrikstad, Norway<br>Tel.: +47 69 35 90 00<br>E-mail: post@jotul.no       |
| <b>Contact address:</b>   | No relevance  |
| <b>AVCP:</b><br><i>System(s) of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V</i> | System 3  |
| <b>Notified body:</b><br><br><b>Test report no:</b>   | RWE Power AG, Feuerstättenprüfstelle<br>NB-No 1427<br>FSPS-Wa 2250-EN                                       |
| <b>Declared performance:</b>  |   |
| <b>Harmonized technical specification</b>   | EN 13240:2001/A2:2004/AC:2007   |
| <b>Essential characteristics</b>  | Performance   |
| <b>Fire safety</b>  | -   |
| Reaction to fire  | A1  |
| Distance to combustible materials   | Minimum distances, in mm<br>Rear = 120<br>Sides = 350<br>Corner = 120<br>Front = 900                        |
| Risk of burning fuel falling out  | No  |
| <b>Emission of combustion products</b>  | CO [0,08 %]<br>NOx [112 mg/m <sup>3</sup> ]<br>OGC [54 mgC/m <sup>3</sup> ]<br>Dust [20 mg/m <sup>3</sup> ] |
| <b>Surface temperature</b>  | Pass  |
| <b>Electrical safety</b>  | -   |
| <b>Cleanability</b>   | Pass  |
| <b>Maximum water operating pressure</b>   | -   |
| <b>Flue gas temperature at nominal heat output</b>  | T [305°C]   |
| <b>Mechanical resistance (to carry a chimney/flue)</b>  | NPD   |
| <b>Thermal output</b>   |   |
| Normal heat output  | 6 kW  |
| Room heating output   | - kW  |
| Water heating output  | -*kW  |
| <b>Energy efficiency</b>  | η [75%]   |

**Declaration:**

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Tom J. Berglind


R&D Manager

*(Name and function)*

Fredrikstad, June 18 2014

*(Place and date of issue)*

*(Signature)*

A handwritten signature in black ink that reads "Tom J. Berglind". The signature is written in a cursive style with a large, looped 'T' and 'B'.