

Declaration of Performance (DoP)



No. F370 AdvanceAT-CPR-160620	
Product Type:	Roomheaters fired by solid fuel
Type, batch or serial number:	Jøtul F 370 Advance AT (F371 Advance AT, F373 Advance AT, F377 Advance AT, F378 Advance AT, F 371 Advance High Top AT, F377 Advance High Top AT, F378 Advance High Top AT)
Notified body:	Danish Technological Institute
NB-No:	1235
Test report no:	300-ELAB-2223-EN
Declared performance:	
Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fuel	Wood logs
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm (F 377 Advance High Top AT)
	Rear = 75 (50)
	Sides = 700 (600)
	Corner = 450 (450)
	Front = 1100 (1100)
	<i>See also the installation instructions</i>
Risk of burning fuel falling out	No
Emission of combustion products	CO [0,05 %] NOx [92 mg/m ³] OGC [32 mgC/m ³] PM [4 mg/m ³]
Surface temperature	Pass
Electrical safety	-
Cleanability	Pass
Maximum water operating pressure	-
Flue gas temperature at nominal heat output	T [255°C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Normal heat output	7 kW
Room heating output	- kW
Water heating output	-*kW
Energy efficiency	η [78%]

Declaration:

The performance of the product in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf of the manufacturer:

Peter

R&D

(Name and function)

Fredrikstad Mai 7, 2016

(Place and date of issue)

A handwritten signature in black ink, appearing to read 'Peter S', written over a horizontal line.

(Signature)